




RGBCCT-840LED/m-DC24V-12MM-25W

SPECIFICATION



840.
LED Qty

24.
Voltage

12.
mm
FPC width

25.
w/m
Power

Product features:

-With RGB (Red, Green, Blue) combined with W (Dual White), can produce a wide spectrum of colors, including pure whites and vibrant hues, making it versatile for various lighting applications.


-High density led chips, brighter and allows for vibrant color blending, ideal for decorative, architectural, or mood lighting

-No flicker, comfortable uniform and ambient lighting, rich and natural colors

-High-quality FPC circuit board, resistant to bending, strong flexibility, easy to shape


-IP grade : IP20, IP65,IP66,IP67,IP68 available

-Long service life, providing 5-year warranty service



Application:

Widely used in hotels, shopping malls, furniture, cabinets, shelves, bars, e-sports game arenas, outdoor lighting landscapes and other scenes, can be used for decorative lighting, direct lighting or indirect lighting



Product parameters:

Basic parameter:


| Color | WL(NM) | RA | Beam angle | Lumen (Lm/m)±5% | Efficiency (l/m/W)±5% | Voltage (V DC) | Electric current (mA/m) | Power(W/m) |
|-------|---------|----|------------|-----------------|-----------------------|----------------|-------------------------|------------|
| R | 620-625 | / | 180° | 100 | 25 | 24V | 167 | 4 |
| G | 520-525 | / | 180° | 581 | 83 | 24V | 292 | 7 |
| B | 465-470 | / | 180° | 156 | 13 | 24V | 167 | 4 |
| C | 6000K | / | 180° | 332 | 83 | 24V | 167 | 4 |
| W | 3000K | / | 180° | 498 | 83 | 24V | 250 | 6 |
| RGBCT | - | / | 180° | 2075 | 83 | 24V | 1042 | 25 |

Other parameters:

| IP grade | Working environment | Storage environment | Length (m) | Max connection Length (m) | LED Qty (pcs/m) | N.W (g/Roll) |
|----------|---------------------|---------------------|------------|---------------------------|-----------------|--------------|
| IP20 | -25°C~+45°C | -30°C~+80°C | 5 | 5 | 840 | 175 |

Packaging parameters:

| Packaging material | A roll(m) | A boxful (roll) | Total Qty(m) | size(mm) | G.W(Kg) |
|--------------------|-----------|-----------------|--------------|----------------|---------|
| Carton | 5 | 100 | 500 | L720*W280*H410 | 18.5 |





QUALITY



HONESTY



SERVE








INNOVATION

Processing custom waterproof process:




Contrast of Process


| IP RATING | STRUCTURE | FEATURE | REMARK |
|-----------|--|---|--|
| IP20 |  | Non-Waterproof | Indoor Use Only |
| IP54 |  | Nano Coated | Thin Film Coating Anti Splash Water Tiny Size Changed (Same Looking as IP20) |
| IP65 |  | Silicone glue Coated Waterproof Suitable for Damp Location | Silicone Glue Coating Dripping Anti Splash Water Tiny Size Changed |
| IP67A |  | Silicone Extrusion Waterproof Suitable for Short-time Wet Location | Extruding Process Suitable for outdoor places without standing water |
| IP67B |  | Silicone Tube Waterproof Suitable for Damp Location | Silicone Empty inside Anti Spray Water Tiny Color Shift |
| IP67C |  | Silicone Extrusion Waterproof Suitable for Short-time Wet Location | Extruding Process Suitable for outdoor places without standing water |
| IP67D |  | U-Tube Instilled Silicone Glue Waterproof Suitable for Short-time Wet Location | Silicone Glue Coating Suitable for outdoor places without standing water |
| IP68A |  | Silicone Tube Injected Silicone Glue Waterproof Suitable for Outdoor and Underwater | 360° Silicone Filling Use for Outdoor and Underwater |
| IP68B |  | Silicone Solid Extrusion Waterproof Suitable for Outdoor and Underwater | 360° Silicone Filling Use for Outdoor and Underwater |

IP code : Ingress Protection Marking, IEC standard 60529

Package:



Installation diagram:



Statements :

- 1). For safety, the product wire should be moved and replaced by the manufacturer, agent or other authorized person.
- 2). Please refer to the product manual before installation.
- 3). Above-refered schematic diagrams are from our standard product. Please subject to your actual product data if there is difference.
- 4). In actual use, we suggest 80% consumption of the driver. Keep 20% as power to start the led strip.
- 5). For safety, no touch the AC terminal.
- 6). Any acidic or alkaline substance is forbidden.
- 7). No notice for updated of this product.



| Problem | Possible reasons | solution |
|--|---|---|
| All fail | ● No power supply | Give power supply. |
| | ● Automatic switch-off because of the open circuit and short circuit | Solve the problem, switch on again. |
| | ● Wrong connection (positive connect with negative) | Check and get right connection. |
| Part fail | ● Part power-supply fail | Check and make sure the power supply well. |
| | ● Part circuit error | |
| | ● Part wrong connection(positive connect negative) | Check and get right connection. |
| Inconsistent brightness or insufficient brightness | ● overload of the driver | Use higher-power driver. |
| | ● Too big power consumption of the switch, or unbalanced power consumption from different strip series. | Keep the strip working voltage is more or less 5% than the Rated voltage. 1.shorten the connection cable length, or change to thicker cable. 2.Make sure the strip quantity is less than the allowed connection quantity.Keep the led strip quantity of each series similar). |
| | ● Too many Led strips connection | Adjust the led strip quantity, make sure sufficient power supply. |
| LED flash | ● Poor welding connection of wires | Check,find and solve it. |
| | ● switch problem | Change to right switch. |