


480LED/m-DC12V/24V-5mm-IP20

SPECIFICATION



480^m
LED Qty

12/24V^v
Voltage

5^{mm}
FPC width



7^{W/m}
Power

Product features:

1. 480 chips arranged linearly, integrated packaging, uniform light color, no light spots
2. High thermal conductivity flexible circuit board design, can be bent freely, easy to install
3. The LED chip is directly mounted on the FPC, with a light emission angle of up to 180 degrees
4. DC12V/24V constant voltage design, safe low voltage, small voltage drop, standard cascade of 5 meters;
5. Back mounted high viscosity thermal conductive double-sided tape, easy to install, firmly and persistently adhered;
6. LED light source, energy-saving and environmentally friendly, in compliance with ROHS environmental standards.


**Application:**

Widely used in hotels, shopping malls, furniture, cabinets, shelf as decoration lighting, direct lighting or indirect lighting



Product parameters:

General parameters		Performance parameters	
Product Model	GL-R1000TF-400xCOB COB 400leds/meter	Lumen(±5%)	420~560lm/m
Color	WW, NW, CW	Efficiency(±5%)	60-80lm/W
CCT	2700K/3000K/4000K/6000K (Special CCT can be customized)	Voltage	DC12/24V
CRI	Ra≥90	Electric current	292-583mA/m
Beam angle	120°	Power	7W/m
Cut Distance	12V 25mm/24V 50mm		
Environmental test parameters		Packaging parameters	
IP grade	IP20	A roll	5m
Working environment	-25 C ~+45 C	N.W(Roll)	80g
Storage environment	-30 C ~+80 C	Qty/Carton	500m-100roll
Max connection Length	5m	Packing size(mm)	L720*W280*H410
		G.W	9Kg



IP Rating:




Contrast of Process


IP RATING	STRUCTURE	FEATURE	REMARK
IP20		Non-Waterproof	Indoor Use Only
IP54		Nano Coated	Thin Film Coating Anti Splash Water Tiny Size Changed (Same Looking as IP20)
IP65		Silicone glue Coated Waterproof Suitable for Damp Location	Silicone Glue Coating Dropping Anti Splash Water Tiny Size Changed
IP67A		Silicone Extrusion Waterproof Suitable for Short-time Wet Location	Extruding Process Suitable for outdoor places without standing water
IP67B		Silicone Tube Waterproof Suitable for Damp Location	Silicone Empty inside Anti Spray Water Tiny Color Shift
IP67C		Silicone Extrusion Waterproof Suitable for Short-time Wet Location	Extruding Process Suitable for outdoor places without standing water
IP67D		U-Tube Instilled Silicone Glue Waterproof Suitable for Short-time Wet Location	Silicone Glue Coating Suitable for outdoor places without standing water
IP68A		Silicone Tube Injected Silicone Glue Waterproof Suitable for Outdoor and Underwater	360° Silicone Filling Use for Outdoor and Underwater
IP68B		Silicone Solid Extrusion Waterproof Suitable for Outdoor and Underwater	360° Silicone Filling Use for Outdoor and Underwater

IP code : Ingress Protection Marking, IEC standard 60529

Package:



Installation diagram:



Statements :

- 1). For safety, the product wire should be moved and replaced by the manufacturer, agent or other authorized person.
- 2). Please refer to the product manual before installation.
- 3). Above-refered schematic diagrams are from our standard product. Please subject to your actual product data if there is difference.
- 4). In actual use, we suggest 80% consumption of the driver. Keep 20% as power to start the led strip.
- 5). For safety, no touch the AC terminal.
- 6). Any acidic or alkaline substance is forbidden.
- 7). No notice for updated of this product.



Problem	Possible reasons	solution
All fail	No power supply	Give power supply.
	Automatic switch-off because of the open circuit and short circuit	Solve the problem, switch on again.
	Wrong connection (positive connect with negative)	Check and get right connection.
Part fail	Part power-supply fail	Check and make sure the power supply well.
	Part circuit error	
	Part wrong connection(positive connect negative)	Check and get right connection.
Inconsistent brightness or insuffiscent brightness	overload of the driver	Use higher-power driver.
	Too big power consumption of the switch, or unbalanced power consumption from different strip series.	Keep the strip working voltage is more or less 5% than the Rated voltage. 1.shorten the connection cable length, or change to thicker cable. 2.Make sure the strip quantity is less than the allowed connection quantity.Keep the led strip quantity of each series similar).
	Too many Led strips connection	Adjust the led strip quantity, make sure sufficient power supply.
LED flash	Poor welding connection of wires	Check,find and solve it.
	switch problem	Change to right switch.